



- *可用在真空系统上。
- *金属部分采用不锈钢(SUS303)，代替传统的黄铜。
- *适合作以下用途：
 - 食品加工机械设备，可能接触洗涤水或盐水的地方。
 - 无铜设备用，例如显像管生产线上等。
 - 洁净房
- *白色主体易于辨别。
- *标准螺纹带密封剂。

外螺直接头：KG2H


连接 T Uni螺纹	适合软管外径mm					
	φ4	φ6	φ8	φ10	φ12	φ16
M3x0.5	KG2H04-M3					
M5x0.8	KG2H04-M5	KG2H06-M5				
M6x1.0	KG2H04-M6	KG2H06-M6				
1/8"	KG2H04-01S	KG2H06-01S	KG2H08-01S	KG2H10-01S	KG2H12-01S	
1/4"	KG2H04-02S	KG2H06-02S	KG2H08-02S	KG2H10-02S	KG2H12-02S	
3/8"		KG2H06-03S	KG2H08-03S	KG2H10-03S	KG2H12-03S	KG2H16-03S
1/2"			KG2H08-04S	KG2H10-04S	KG2H12-04S	KG2H16-04S

* 脱离环可选颜色：灰、蓝、黑，详细产品尺寸请参照KQ2H尺寸图。

内六角接头：KG2S


连接 T Uni螺纹	适合软管外径mm					
	φ4	φ6	φ8	φ10	φ12	φ16
M3x0.5	KG2S04-M3					
M5x0.8	KG2S04-M5	KG2S06-M5				
M6x1.0	KG2S04-M6	KG2S06-M6				
1/8"	KG2S04-01S	KG2S06-01S	KG2S08-01S	KG2S10-01S	KG2S12-01S	
1/4"	KG2S04-02S	KG2S06-02S	KG2S08-02S	KG2S10-02S	KG2S12-02S	
3/8"		KG2S06-03S	KG2S08-03S	KG2S10-03S	KG2S12-03S	KG2S16-03S
1/2"			KG2S08-04S	KG2S10-04S	KG2S12-04S	KG2S16-04S

* 脱离环可选颜色：灰、蓝、黑，详细产品尺寸请参照KQ2S尺寸图。

外螺弯接头：KG2L


连接 T Uni螺纹	适合软管外径mm					
	φ4	φ6	φ8	φ10	φ12	φ16
M3x0.5	KG2L04-M3					
M5x0.8	KG2L04-M5	KG2L06-M5				
M6x1.0	KG2L04-M6	KG2L06-M6				
1/8"	KG2L04-01S	KG2L06-01S	KG2L08-01S	KG2L10-01S	KG2L12-01S	
1/4"	KG2L04-02S	KG2L06-02S	KG2L08-02S	KG2L10-02S	KG2L12-02S	
3/8"		KG2L06-03S	KG2L08-03S	KG2L10-03S	KG2L12-03S	KG2L16-03S
1/2"			KG2L08-04S	KG2L10-04S	KG2L12-04S	KG2L16-04S

* 脱离环可选颜色：灰、蓝、黑，详细产品尺寸请参照KQ2L尺寸图。